

Ceiling lamp HERMETIK LED SMD



Basic data

- external dimensions: 1260/110/90 mm
- body made of ABS (acrylonitrile butadiene styrene)
- shader made of PS (polystyrene)
- transparent shader of low light attenuation
- index of protection: **IP65**
- dust- and waterproof body
- easily adaptable to through wiring
- resistant to vast range of working temperature
- Light source lifespan: **approx. 60 000 hours**
- warranty: 3 years



Light source power consumption	Light source luminous flux	Light source efficiency	Light colour
18 W	2 160 lm	120 lm/W	3 000 K
18 W	2 280 lm	127 lm/W	4 000 K
18 W	2 400 lm	133 lm/W	6 000 K
36 W	4 320 lm	120 lm/W	3 000 K
36 W	4 560 lm	127 lm/W	4 000 K
36 W	4 800 lm	133 lm/W	6 000 K

Microwave Motion Sensor Version

All versions can be equipped with electronic Microwave Motion Sensor (MMS). Microwave Motion Sensor's parameters:

- detection angle: 360 degrees
- adjustable dusk to dawn sensor: 2 - 2000lx
- adjustable time setting: 8sec - 12min
- adjustable detection distance: Φ 1 - 16m
- all adjustable rates set independently

All versions of voltage 230V also available in DMMS version (equipped with electronic microwave motion sensor with dimming function). Ask our sales representative about details.